

DKS ACCESSORIES

ILLUSTRATION	ITEM #	DESCRIPTION
	SAC-5	Strap Anchor Dimensions: 1"W x 1"H x 5"L Five $\frac{3}{16}$ " Nailing Holes Thickness: 18 Ga.
	MASONRY TUBE ANCHORS	Masonry Tube Anchor $\frac{3}{4}$ " EMT Tubing 2" Strap Width Thickness: 16 Ga. MAS575-4 for 5 $\frac{3}{4}$ " Unequal Rabbet MAS625-6 for 6 $\frac{1}{4}$ " Unequal Rabbet MAS675-3 for 6 $\frac{3}{4}$ " Unequal Rabbet MAS775-2 for 7 $\frac{3}{4}$ " Unequal Rabbet MAS825-5 for 8 $\frac{1}{4}$ " Unequal Rabbet MAS875-1 for 8 $\frac{3}{4}$ " Unequal Rabbet
	MASONRY T ANCHORS	Masonry Tee Anchor 1" Round Holes $\frac{1}{4}$ " Locking Flange Thickness: 16 Ga. TANC5581 for 5 $\frac{3}{4}$ " Frame TANC6584 for 6 $\frac{3}{4}$ " Frame TANC7583 for 7 $\frac{3}{4}$ " Frame TANC8582 for 8 $\frac{3}{4}$ " Frame
	EX-BOLT	Expansion Bolt Anchor 1" Dia. Hole
	EX-BOLT-58	Expansion Bolt Anchor $\frac{5}{8}$ " Dia. Hole
	EMA-634	Existing Masonry Anchor For 4 $\frac{3}{4}$ " – 6 $\frac{3}{4}$ " Frames Best for existing wall applications

DKS ACCESSORIES

ILLUSTRATION	ITEM #	DESCRIPTION
	PRECLAM-8	Drywall Compression Anchor ¼" – 20 x 1" Machine Screw
	WS575 WS625 WS675 WS7125 WS775 WS825 WS875	Wood Stud Anchor Welded Type Thickness: 18 Ga. Wood Stud Anchor for 5 ¾" Frame Wood Stud Anchor for 6 ¼" Frame Wood Stud Anchor for 6 ¾" Frame Wood Stud Anchor for 7 ½" Frame Wood Stud Anchor for 7 ¾" Frame Wood Stud Anchor for 8 ¼" Frame Wood Stud Anchor for 8 ¾" Frame
	MPSA-15	Multi-Purpose Stud Anchor for Double Egress Frame Fits standard double egress sizes
	MPAA-10	Multi-Purpose Adjustable Anchor (2 per set) Can be used as a single 8 ¾" wood/metal stud or complete opening anchor
	HDADWA	Heavy Duty Adjustable Drywall Anchor (2 per set) Thickness: 18 Ga. Fits frame sizes 5 ¾" to 8 ¾"
	LADWA-11	Large Adjustable Drywall Anchor (2 per set) Thickness: 18 Ga. Fits frame 7" to 12" Anchor marked with different frame sizes

DKS ACCESSORIES

ILLUSTRATION	ITEM #	DESCRIPTION
	ADWA-12	Adjustable Drywall Anchors (2 per set) For 4 3/4" to 6 3/4" frames
	MAS01	Wire Masonry Anchor
	SS575 SS775 SS825	Steel Stud Anchor Welded Type Thickness: 18 Ga. Steel Stud for 5 3/4" Frame Steel Stud for 7 3/4" Frame Steel Stud for 8 3/4" Frame
	SFA-834	Sidelite Floor Anchor Fits frame sizes from 4 3/4" to 8 3/4"
	AFANC-22	Adjustable Floor Anchor Thickness: 16 Ga.
	FA-L	Large Floor Anchor Thickness: 18 Ga. For 7 3/4" to 9 3/4"
	FA-S	Small Floor Anchor Thickness: 18 Ga. For 4 3/4" to 6 3/4" Frames
	FA-HD	Heavy Duty Floor Anchor Dimensions: 5 1/4"W x 2 3/8"H

DKS ACCESSORIES

ILLUSTRATION	ITEM #	DESCRIPTION
	RMC-13	Removable Mullion Clip
	AMBA-14	Adjustable Mullion Base Anchor Fits frames from 4 3/4" to 8 3/4"
	TB-14	Thru-Bolt 3/4" Dia. For doors 1 3/4" or less. Best used for latch protectors, door savers, louvers, etc...
	DY-5	Stud Dynabolt Anchor 5" Long x 3/8" Dia.
	SBA-438	Stud Bolt Anchor 4" Long x 3/8" Dia.
	SBA-382	Stud Bolt Anchor 2" Long x 3/8" Dia.
	WSA-4	Wood Lag Screw 4" Long 3/8" Dia.
	WD-6	Wood Lag Screw 6" Long 3/8" Dia.
	PPB-16	3/4" Plastic Plug Button