

**16 GAUGE
GALVANIZED
STOCK REVERSIBLE SEAMLESS POLYSTYRENE/HONEYCOMB FLUSH DOORS**

- Includes closer reinforcement, fire label WHI 3HR positive pressure (S) smoke label.
- *Galvanized, Flushed Top Inverted Bottom
- 12 Gauge Closer Reinforcement, 7 Gauge Hinge Reinforcement
- Square Edged, Non-Handed
- Choice of 3 Standard Lock Reinforcements (Cylindrical, FED 86 Edge, Blank PB Reinforced)

UP TO 8'0 TALL DOORS

Item#	Size	Type/ Gauge	Prep
1622	3068	*16G	C
1601			MB
1603			BR
1604	3070	*16G	C
1608			MB
1611			BR
1614	3080	*16G	C
1617			MB
1620			BR
1677	3470	*16G	C
1678			MB
1679			BR
1649	3670	*16G	C
1650			MB
1652			BR
1661	3680	*16G	MB
1656	3870	*16G	C
1657			MB
1658			BR
1654	4070	*16G	C
1655			MB
1659			BR



9'0 TALL DOORS

NON-STOCK, SPECIAL FACTORY ORDER			
Item#	Size	Type/ Gauge	Prep
1680	3090	*16G	C
1681			MB
1682			BR
1683	3490	*16G	C
1684			MB
1685			BR
1686	3690	*16G	C
1687			MB
1688			BR
1689	3890	*16G	C
1690			MB
1691			BR
1692	4090	*16G	C
1693			MB
1694			BR




▶ 3/8" Bottom Undercut

1600 Series Flush Doors

Prepared for Continuous Hinge Application

STOCK REVERSIBLE CORNER SEAM POLYSTYRENE FLUSH DOORS

- 15/32" undercut on door width to fit most major manufacturers continuous hinge prep.
- Includes closer reinforcement, fire label and WHI 3 hour positive pressure  smoke label.

16 GAUGE GALVANIZED		
Item#	Size	Prep
G1608CH	3070	MB
G1611CH		BR
G1649CH	3670	C
G1650CH		MB
G1654CH	4070	C
G1655CH		MB