

4100 Series Masonry Frames

June 2013

COMPLETE FRAMES

14 GAUGE GALVANIZED MASONRY UN-EQUAL RABBET

S I N G L E	WIDTH	HEIGHT	DEPTH					
	2'0", 2'4"	6'8"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
		7'0"						
	2'6", 2'8"	7'2"						
	2'10", 3'0"	8'0"						
F R A M E S	3'1", 3'6"	6'8"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
		7'0"						
	3'8", 3'10"	7'2"						
		8'0"						
	4'0"	8'1" - 10'0"						
D O U B L E	4'0", 4'8"	6'8"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
		7'0"						
	5'0", 5'4"	7'2"						
		8'0"						
	5'8", 6'0"	8'1" - 10'0"						
F R A M E S	6'1", 7'0"	6'8"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
		7'0"						
	7'4", 7'8"	7'2"						
		8'0"						
	8'0"	8'1" - 10'0"						

14 GAUGE GALVANIZED FRAMES COMPONENTS

HINGE JAMBS	DEPTH					
6'8"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
7'0"						
7'2"						
8'0"						
8'1" - 10'0"						
STRIKE JAMBS						
6'8"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
7'0"						
7'2"						
8'0"						
8'1" - 10'0"						
SINGLE HEAD						
2'0" - 3'0"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
3'1" - 4'0"						
PAIR HEAD						
4'0" - 6'0"	4.25"-5.75"	5.875"-6.75"	6.875"-7.75"	7.875"-8.75"	8.875"-9.75"	9.875"-13.00"
6'1" - 8'0"						

In stock depths: 4.75" and 7.75"

- Other Jamb depths are available with lead time. Consult factory. Fire label WHI 3HR Positive Pressure,  smoke label.

- Masonry frames are prepared for ASA strike.

- Includes anchors. Please specify type.

ANCHORS: **WS** = Wood Stud, **SS** = Steel Stud, **MA** = Masonry Wire

