

NOV 2019

IN STOCK FOR IMMEDIATE SHIPPING

GLASS ... IN STOCK GLASS / ACCESSORIES

VISION LITE NARROW & STANDARD PROFILE, 1/4" & 3/16" GLASS THICKNESS


Glass sizes are measured 1" less than the cut out size

TEMP (Tempered Glass)

- Heat-treated clear safety glass that breaks into small particles when broken.
- Light Transmission: 86% approx
- Thickness: 1/4" (6 mm)
- Non-Fire Rated
- Size: Minimum 2" x 2", max sheet size: 88" x 118"

PPF (PYRAN® PLATINUM F, Fire & Safety Rated)

- Fire-Rated up to 90 minutes (180 minutes in doors) with required hose stream test
- Fire and Safety-Rated Glass Impact / Safety Rated to ANSI Z97.1 and CPSC 16CFR1201 CAT II
- Thickness: 3/16" (5mm). Weight: 2.5 lbs / ft.2
- Premium glass-ceramic with surface applied heavy duty film
- Transparent and wireless with light transmission at 80% approx.
- Certified C2C-Silver by MBDC and is listed in the EPA's Environmentally Preferable Purchasing (EPP) database
- and can earn LEED points
- Maximum sheet size: 43" x 77"



WS (PROTECT3™ Wired Safety Glass, Fire Rated)

- Fire Rated up to 90 minutes with hose stream
- UL classified and UL labeled
- Impact-safety rated to ANSI Z97.1 and CPSC 16CFR1201 CAT I and II
- Passes 400 ft-lb impact tests
- Passes air blast testing minimum Level 3 @ 4.0PSI
- Embedded $\frac{3}{4}$ x $\frac{3}{4}$ wire mesh
- Light Transmission: 86% approx
- Thickness: 1/4" (6 mm)
- · Annealed single glazing with safety film applied to one side

| | INSTOCKSIZES FOR IMMEDIATE SHIPPING | | DIATE SHIPPING |
|-------------|-------------------------------------|--------|--|
| GLASS SIZES | TEMP (¼") | WS(¼") | PPF (³ / ₁₆ ") |
| 4" x 34" | TEMP434 | WS434 | PPF434 |
| 5" x 25" | | | PPF525 |
| 5" x 26" | TEMP526 | WS526 | PPF526 |
| 5" x 71" | | | PPF571 |
| 6" x 21" | TEMP621 | WS621 | PPF621 |
| 7" x 17" | | WS717 | |
| 7" x 29" | | WS729 | |
| 7" x 31" | TEMP731 | WS731 | |
| 7" x 35" | TEMP735 | WS735 | |
| 11" x 11" | TEMP1111 | WS1111 | PPF1111 |
| 23" x 23" | TEMP2323 | WS2323 | |
| 23" x 29" | TEMP2329 | WS2329 | PPF2329 |
| 23" x 31" | TEMP2331 | WS2331 | |
| 23" x 35" | TEMP2335 | WS2335 | |
| 23" x 63" | TEMP2363 | WS2363 | |

Use of glazing compound or glazing tape on both sides recommended to minimize breakage. Install in fire listed vision frames.

Prices above do not include Glazing Tape. Black Glazing Tape: 1/16" x 3/8" x 150': \$39.00 list per roll, item # "GT"

See page II for packaging and handling charges.