



DKS Fire Rated Steel Vision Lite Kits

Series: SVL & VL Vision Lites

Product Description:

DKS Fire Rated Steel Vision Lite Kits for use in listed and labeled fire rated hollow metal door applications, positive and neutral pressure.

Rating	Maximum Area (Clear View)	Maximum Height	Maximum Width	Glazing	Door type
Up to 45 Minutes	660 sq.in.	30"	22"	Listed Fire rated 1/4" to 1" thick, Wired or Ceramic Glazing	Steel
Up to 90 Minutes	100 sq.in.	33"	10"	Listed Fire rated 1/4" to 1" thick, Wired or Ceramic Glazing	Steel
Up to 180 Minutes	100 sq.in.	33"	10"	Listed Fire rated 3/16" to 1" thick, Ceramic Glazing	Steel

AVAILABLE INVENTORIES WITH FIRE RATINGS

FRAME SIZE (width x height)	CLEAR VIEW AREA (VISIBLE VIEW) sq. in.	45 MIN	90 MIN	180 MIN
		22" X 30" MAX (width x height) 600 sq.in. MAX VISIBLE VIEW	10" X 33" MAX (width x height) 100 sq.in. MAX VISIBLE VIEW	10" X 33" MAX (width x height) 100 sq.in. MAX VISIBLE VIEW
5" x 20"	54	WS / PPF	WS / PPF	PPF
5" x 35"	99	WS / PPF	-	-
6" x 14"	48	WS / PPF	WS / PPF	PPF
6" x 24"	88	WS / PPF	WS / PPF	PPF
6" x 26"	96	WS / PPF	WS / PPF	PPF
6" x 27"	100	WS / PPF	WS / PPF	PPF
6" x 30"	112	WS / PPF	-	-
6" x 36"	136	WS / PPF	-	-
7" x 22"	100	WS / PPF	WS / PPF	PPF
8" x 18"	96	WS / PPF	WS / PPF	PPF
8" x 30"	168	WS / PPF	-	-
8" x 32"	180	WS / PPF	-	-
8" x 36"	204	WS / PPF	-	-
8" x 38"	216	WS / PPF	-	-
12" x 12"	100	WS / PPF	-	-
18" x 18"	256	WS / PPF	-	-
18" x 30"	448	WS / PPF	-	-

WS - Wire Shield, 1/4" thick wired glass with film. Fire rating: 20-90 minutes

PPF - Pyran, 3/16" thick ceramic glass with surface applied heavy duty safety film. Fire rating: 20-180 minutes.