

# **GLASS** IN STOCK GLASS / ACCESSORIES

#### IN STOCK FOR IMMEDIATE SHIPPING

VISION LITE NARROW & STANDARD PROFILE, 1/4" & 3/16" GLASS THICKNESS

Glass sizes are measured 1" less than the cut out size

#### TEMP (Tempered Glass)


- Heat-treated clear safety glass that breaks into small particles when broken.
- Light Transmission: 86% approx
- Thickness: 1/4" (6 mm)
- Non-Fire Rated
- Size: Minimum 2" x 2", max sheet size: 88" x 118"

## PPF (PYRAN® PLATINUM F, Fire & Safety Rated)


- Fire-Rated up to 90 minutes (180 minutes in doors) with required hose stream test
- Fire and Safety-Rated Glass Impact / Safety Rated to ANSI Z97.1 and CPSC 16CFR1201 CAT II
- Thickness: 3/16" (5mm). Weight: 2.5 lbs / ft.2
- Premium glass-ceramic with surface applied heavy duty film
- Transparent and wireless with light transmission at 80% approx.
- Certified C2C-Silver by MBDC and is listed in the EPA's Environmentally Preferable Purchasing (EPP) database and can earn LEED points
- Maximum sheet size: 43" x 77"

### WS (PROTECT3™ Wired Safety Glass, Fire Rated)

- Fire Rated up to 90 minutes with hose stream
- UL classified and UL labeled
- Impact-safety rated to ANSI Z97.1 and CPSC 16CFR1201 CAT I and II
- Passes 400 ft-lb impact tests
- Passes air blast testing minimum Level 3 @ 4.0PSI
- Embedded <sup>3</sup>/<sub>4</sub>" x <sup>3</sup>/<sub>4</sub>" wire mesh
- Light Transmission: 86% approx
- Thickness: 1/4" (6 mm)
- · Annealed single glazing with safety film applied to one side



**TEMPERED** 



PYRAN

WIRESHIELD

INSTOCK SIZES
GLASS SIZES
4" x 34" (TEMP, WS, PPF)
5" x 25"(PPF)
5" x 26" (TEMP, WS, PPF)
5" x 71" (PPF)
6" x 21" (TEMP, WS, PPF)
7" x 17" (WS)
7" x 29" (WS)
7" x 31" (TEMP, WS)
7" x 35" (TEMP, WS)
11" x 11" (TEMP, WS, PPF)
23" x 23" (TEMP, WS)
23" x 29" (TEMP, WS, PPF)
23" x 31" (TEMP, WS)
23" x 35" (TEMP, WS)
23" x 63" (TEMP, WS)
See pages LL12 - LL14 for list of custom cut sizes. Call our Customer Service for unlisted sizes.

Use of glazing compound or glazing tape on both sides recommended to minimize breakage. Install in fire listed vision frames. Above do not include Glazing Tape. Black Glazing Tape: 1/16" x 3%" x 150', item # "**GT**"